

Art. FDFSH6A

Telecamera Fisheye 6 Megapixel



Model	DH-IPC-EB5500
Camera	
Image Sensor	1/3" 5Megapixel progressive scan CMOS
Effective Pixels	2592(H)x1944(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3(4)~1/100000s
Min. Illumination	0.01lux/F2.6(color) ,0.001Lux@F2.6(B/W)
S/N Ratio	More than 50dB
Video Output	N/A
Camera Features	

Max. IR LEDs Length	N/A
Day/Night	Auto(Electronic)/Color/B/W
Backlight Compensation	BLC/HLC/DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	1.42mm
Max Aperture	F2.6
Focus Control	Manual
Angle of View	H:185°
Lens Type	Fixed lens
Mount Type	Board-in Type
Video	
Compression	H.264/ MJPEG



Resolution	5M(2560'1920)/3M(2048×1520)/UXGA(1600×1200)/1.3M(1280×960)/720P(1280×720)/D1(704×576/704×480)/CIF(352×288/352×240)	
Frame Rate	Main Stream	5M(1~12fps)/ UXGA (1 ~ 25/30fps)
	Sub Stream	D1/CIF(1 ~ 25/30fps)
	Bit Rate	H.264: 20K ~ 8192Kbps
Audio		
Compression	G.711a/G.711u/PCM	
Interface	1/1 channel In/Out(Built in Mic)	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Wi-Fi	N/A	
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
Compatibility	ONVIF,PSIA,CGI	
Max. User Access	20 users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
Auxiliary Interface		
Memory Slot	Micro SD, Max 64GB	
RS485	N/A	



Alarm	1/1 channel In/Out
PIR Sensor Range	N/A
General	
Power Supply	DC12V,PoE
Power Consumption	Max 6W
Working Environment	-30°C~+60°C, Less than 95% RH
Ingress Protection	N/A
Vandal Resistance	IK10
Dimensions	Φ110mm×54mm
Weight	0.25kg